



PR No. 1000038187

Rfx No.6100001707

Technical Specification for 193nm Excimer Laser system to be coupled with the existing Q-ICPMS

Sr No.	Detailed Specification	Qty	Compliance (Yes/No)
1	<p><u>Specification</u></p> <p>1) 193 nm Excimer Laser: The 193nm Excimer Laser system to be coupled with the existing Quadrupole ICPMS (iCAP) is required to enable rapid analysis of solid mineralogical samples/ rock samples/ fossil samples/ archeological samples/ metallurgical samples with high throughput.</p> <p>2) Laser Source: 193nm Excimer Laser source coherent (Air-cooled); <5 ns pulse width; 1-500Hz repetition rates; Integrated energy control unit in closed-loop for the stabilization of beam energy.</p> <p>3) Beam Delivery System: Capable for circular, square and rectangular ablations with flat craters. Externally homogenized beam for generating every possible crater size from 1-200μm. Fluence ≥ 15 J cm⁻² of energy density at the sample surface. Option for setting the energy output in percentage or J cm⁻². Aperture system for giving square and rectangular ablations while performing imaging. Dynamic focusing during ablation is preferable.</p> <p>4) Viewing system: Full HD digital camera with up to 12.5x objective-to-camera magnification with a secondary macro navigation system having field of view up to 30 mm.</p> <p>5) Lighting system: Software operated high intensity LED light sources such as transmitted, ring and independently-operated coaxial light. The system should have provision for reflected and polarized light source.</p> <p>6) Ablation Chamber and Stages: High performance two-volume sample chamber for analysis and accommodation of large and small sample types. High speed stage featuring minimum 100 mm x 100 mm XY with up to 50 mm Z focus. The resolution</p>	1 No.	



INDIAN INSTITUTE OF TECHNOLOGY BOMBAY
MATERIALS MANAGEMENT DIVISION
Powai, Mumbai - 400076

	<p>of travel back to initial position should be $<1\mu\text{m}$.</p> <p>7) Gas Handling: Internal gas control for Argon, Helium and Nitrogen, including integrated Mass Flow Controller (MFC). The system should be capable of having an extra MFC for the addition of N_2 up to 100 ml/minute.</p> <p>8) Sampling system and sample holders: Glass Signal Smoother, laser spot size enhancer and flexible shutter modes, sample insert holder: (a) Mount (1 inch) only (3 x 3); (b) Combination of 3 mounts (1 inch) and 3 thin sections (27mm x 46mm) and (c) six thin sections (27mm x 46 mm).</p> <p>9) DCI: Dual Concentric Injector for ultra-fast washout speeds</p> <p>10) PC and Software: Integrated control PC and software featuring sample image import capability; software-controlled turret assembly for automatic switching between laser objective and viewing objective.</p> <p>11) Dimensions: Compact standalone system having dimensions up to 100 cm x 100 cm x 200 cm (D x W x H). The model should be equipped for mobility but also have a stable frame.</p> <p>12) Power: 220–240V (AC), 3A, 50/60Hz.</p> <p>13) Coupling unit with existing Q-ICPMS: Connectivity kit including tygon tubing and bi-directional trigger cables for Q-ICPMS and MC-ICPMS.</p> <p>14) Premix and He gas: Vendor should supply premix gas and high purity Helium (He) required for the system during installation.</p> <p>15) Installation and Training: Installation and advanced applications training at the site for one week.</p> <ul style="list-style-type: none">a. Onsite training for operation and maintenance of the instrument immediately after installation. No supplementary payment for travel, boarding, and lodging for the trainer.b. Vendor should include in their tender, provision for maintenance tools and		
--	---	--	--



INDIAN INSTITUTE OF TECHNOLOGY BOMBAY
MATERIALS MANAGEMENT DIVISION
Powai, Mumbai - 400076

	<p>initial stock of maintenance spares that are essential for the proper operation and maintenance of equipment. Full particulars of spare parts should be provided and the cost of the same should be included in the price bid.</p> <p>c. The vendor should be fully responsible for the manufacturer warranty with respect to proper design, quality, and workmanship of all the equipment accessories, etc. covered by the tender.</p> <p>16) Service Support:</p> <p>a) Remote assistance with the same-day response.</p> <p>b) Telephone/mail assistance when the user has sufficient knowledge to attempt minor repairs.</p> <p>c) Maximum onsite response time of <u>FIVE (5)</u> working days for both hardware and software-related problems.</p> <p>d) Provide the list of users in India, emphasizing reputed Earth Sciences departments, with their contact details.</p> <p>17) Analytical Capability Test: During the technical evaluation, the supplier would be requested to demonstrate (in India) the operational capabilities of the instrument within acceptable accuracy and precision (<10 %) for trace elements on NIST glass standards.</p> <p>18) Performance Specifications: The vendor must have installed a minimum of THREE (3) equipment's of similar technology and comparable capacity LASER ABLATION SYSTEM with ICP-MS within India for geological applications in the past TEN (10) years.</p> <p>19) Warranty: Two-year standard warranty from the date of installation.</p> <p>20) Additional add-ons: Iolite and Glitter software for the reduction of LA-ICP-MS data.</p> <p>21) Consumables:</p> <p>(a) NIST Glass reference standards: NIST 610, NIST 611, NIST 612, NIST 614</p>		
--	---	--	--



**INDIAN INSTITUTE OF TECHNOLOGY BOMBAY
MATERIALS MANAGEMENT DIVISION
Powai, Mumbai - 400076**

	<p>(b) USGS reference standards: USGS MRM BCR-2G, USGS MRM NKT-1G, USGS MRM BIR-1G, USGS MRM AGV-2G, USGS MRM MASS-1, USGS MRM GSE-1G, USGS MRM MACS-3, and USGS MRM BHVO-2G</p> <p>(c) Other reference standards: Z91500 zircon standard, Plêsovice zircon standard.</p>		
--	---	--	--

Important Note:

The award of Tender will be finalized only after obtaining the requisite approval from Ministry of Education.